


|   |                          |                                   |
|---|--------------------------|-----------------------------------|
|  | Standard                 | <b>Date:</b><br><b>15.01.2010</b> |
|   | <b>Safety Data Sheet</b> | Version 1                         |
|   |                          | Page: 1 / 6                       |

### 1. PRODUCT AND COMPANY IDENTIFICATION

|                                   |   |
|-----------------------------------|---|
| <b>Generic product name</b>       | : URSA GLASSWOOL  |
| <b>Recommended use</b>            | : Thermal and/or acoustical insulation of wall or roof  |
| <b>Producer</b>                   | : URSA Chudovo LLC<br>10 Vosstania street, Chudovo, Tel.: +7 812 3137272<br>Novgorod region, 174210, Fax: +7 812 3137273<br>Russia Email: Andrey.kashabin@uralita.com |
| <b>Emergency telephone number</b> | : n/a   |

### 2. HAZARDS IDENTIFICATION

|                               |   |
|-------------------------------|---|
| <b>Most important hazards</b> | : There is no hazard statement associated with this product |
| <b>Specific hazards</b>       | : Non applicable  |

### 3. COMPOSITION / INFORMATIONS on INGREDIENTS

| Substance                   | C.A.S. number <sup>(4)</sup> | Amount weight (%) | Classification and labelling (Regulation (CE) n°1272/2008) <sup>(2)</sup> | Classification and labelling (European directive 67/548/EEC) <sup>(3)</sup> |
|-----------------------------|------------------------------|-------------------|---|---|
| Mineral wool <sup>(1)</sup> |                              | 90 – 100%         | Not classified <sup>(2)</sup>   | Not classified  |
| terpolymer binder           |                              | 0 – 10%           | Not classified  | Not classified  |


(1): Man-made vitreous (silicate) fibres with random orientation with alkaline oxide and alkali earth oxide (Na<sub>2</sub>O+K<sub>2</sub>O+CaO+MgO+BaO) content greater than 18% by weight and fulfilling one of the nota Q conditions

(2): Non classified H351 “suspected of causing cancer”. Glass fibres are not classified carcinogenic according to the note Q of the Directive 97/69/EEC and the regulation n° 1272/2008 (page 335 of the JOCE L353 of December 31, 2008)

(3): Where substances are classified in accordance with Regulation (EC) No 1272/2008 during the period from its entry into force until 1 December 2010, that classification may be added in the safety data sheet together with the classification in accordance with Directive 67/548/EEC. From 1 December 2010 until 1 June 2015, the safety data sheets for substances shall contain the classification according to both Directive 67/548/EEC and Regulation (EC) No 1272/2008 (art. 57 of Regulation (CE) 1272/2008, Official journal L353, p. 27)

(4): C.A.S. : Chemical Abstract Service

**Possible facing materials:** glass mat, or polyester mat or aluminium or Kraft paper.

|   |                          |                                   |
|---|--------------------------|-----------------------------------|
|  | Standard                 | <b>Date:</b><br><b>15.01.2010</b> |
|   | <b>Safety Data Sheet</b> | Version 1                         |
|   |                          | Page: 2 / 6                       |

#### 4. FIRST AID MEASURES

##### Information according to the different exposure route:

- Inhalation** : Remove from exposure. Rinse the throat and blow nose to clear dust
- Skin contact** : If mechanical irritation occurs, remove contaminated clothing and wash skin gently with cold water and soap.
- Eyes contact** : Rinse abundantly with water for at least 15 minutes.
- Ingestion** : Drink plenty of water if accidentally ingested.

If any adverse reaction or discomfort continuous from any of the above exposure, seek medical professional advise.

#### 5. FIRE FIGHTING MEASURES

- Suitable extinguishing media** Products do not pose a fire hazard in use; however, some packaging materials or facings may be combustible. Suitable extinguishing media; water, foam, carbon dioxide (CO<sub>2</sub>), and dry powder. In large fires in poorly ventilated areas or involving packaging materials respiratory protection / breathing devices may be required. Products of combustion from product and packaging - carbon dioxide, carbon monoxide and some trace gases such as ammonia, nitrogen oxides and volatile organic substances

#### 6. ACCIDENTAL RELEASE MEASURES


- Personal precautions** : In case of presence of high concentrations of dust, use the same personal protective equipment as mentioned in section 8.
- Environmental protection** : Not relevant
- Methods for cleaning up** : Vacuum cleaner or dampen down with water spray prior to brushing up.

#### 7. HANDLING AND STORAGE

##### Handling

- Technical measures** : No specific measure. Use preferably a knife. If a power tool, it must be equipped with efficient air suction.
- Precaution** : Ensure adequate ventilation of workplace. See section 8
- Safe handling advice** : Avoid unnecessary handling of unwrapped product. See section 8.

The European Regulation (ER) on Chemicals N° 1907/2006 (REACH) enforced on June 1<sup>st</sup> 2007 requires Material Safety Data Sheet (MSDS) only for hazardous substances and mixtures/preparations. Mineral wool products (panels or rolls), are articles under REACH and therefore, MSDS is not legally required. Nevertheless, URSA Insulation decides to provide its customers with the appropriate information for assuring safe handling and use of mineral wool

|   |                          |                                   |
|---|--------------------------|-----------------------------------|
|  | Standard                 | <b>Date:</b><br><b>15.01.2010</b> |
|   | <b>Safety Data Sheet</b> | Version 1                         |
|   |                          | Page: 3 / 6                       |

### Storage

- Technical measures** : No specific measure, palletised products should be stored in accordance with site specific risk assessment.
- Suitable storage condition** : Store products removed from pallet and packaging or loose un-palletised product, in a dry location
- Incompatible materials** : none
- Packaging material** : Delivered packed in polyethylene film or cardboard on wooden pallet

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

**Exposure Limit Value** : None at European level.  
Country limits: 4 mg/m<sup>3</sup> for total dust.

**Exposure controls** : No specific requirements

### Individual protection equipments

**Respiratory protection** : When working in unventilated area or during operations which can generate emission of any dust, wear disposable face mask. Type in accordance with EN 149 FFP1 is recommended.

**Hand protection** : Wear usual gloves in conformity with EN 388

**Eyes protection** : Wear goggles when working overhead. Eye protection to EN 166 is advised

**Skin protection** : Cover exposed skin

**Hygiene measures** : Rinse in cold water before washing

The following sentence and pictograms are printed on packaging

*"The mechanical effect of fibres in contact with skin may cause temporary itching"*



Ventilate working area if possible



Waste should be disposed of according to local regulations



Cover exposed skin. When working in unventilated area wear disposable face mask



Clean area using vacuum equipment




Wear goggles when working overhead



Rinse in cold water before washing

The European Regulation (ER) on Chemicals N° 1907/2006 (REACH) enforced on June 1<sup>st</sup> 2007 requires Material Safety Data Sheet (MSDS) only for hazardous substances and mixtures/preparations. Mineral wool products (panels or rolls), are articles under REACH and therefore, MSDS is not legally required. Nevertheless, URSA Insulation decides to provide its customers with the appropriate information for assuring safe handling and use of mineral wool

|   |                          |                                   |
|---|--------------------------|-----------------------------------|
|  | Standard                 | <b>Date:</b><br><b>15.01.2010</b> |
|   | <b>Safety Data Sheet</b> | Version 1                         |
|   |                          | Page: 4 / 6                       |


## 9. PHYSICAL AND CHEMICAL PROPERTIES

|   |  |
|---|--|
| <b>Physical state</b>   | : Solid  |
| <b>Form</b>   | : Roll or panel                                      |
| <b>Colour</b>   | : White  |
| <b>Odour</b>  | : Odourless  |
| <b>pH</b>   | : Not applicable                                     |
| <b>Boiling point</b>  | : Not relevant                                       |
| <b>Flash point</b>  | : Not relevant                                       |
| <b>Flammability</b>   | : Not relevant                                       |
| <b>Explosive properties</b>   | : Not relevant                                       |
| <b>Density</b>  | : From 10 to 30 kg/m <sup>3</sup>                    |
| <b>Water solubility</b>   | : Generally chemically inert and insoluble in water. |
| <b>Fat solubility</b>   | : Not applicable                                     |
| <b><u>Others information</u></b>  |  |
| <b>Approximate Length weight geometric mean diameter of fibres:</b> 3 to 5 µm |  |
| <b>Length weight geometric mean diameter less 2 standard errors*:</b> < 6 µm  |  |
| <b>Orientation of fibres</b>  | : Random   |
| *: Regulation (EC) 1272/2008, nota R  |  |

## 10. STABILITY AND REACTIVITY

|  |   |
|--|---|
| <b>Stability</b>                         | : <b>For building:</b> Stable in normal conditions of use<br><b>For high T uses:</b> Binder will start to decompose around 200°C  |
| <b>Dangerous reactions</b>               | : None in normal conditions of use  |
| <b>Hazardous decomposition products:</b> | <b>For building:</b> None in normal condition of use.<br><b>For high T uses:</b> Decomposition of binder around 200°C produces carbon dioxide and some trace gases. The duration and amount of release is dependant upon the thickness of the insulation, binder content and the temperature applied. During first heating, good ventilation or appropriate personal protection equipment are required. |

The European Regulation (ER) on Chemicals N° 1907/2006 (REACH) enforced on June 1<sup>st</sup> 2007 requires Material Safety Data Sheet (MSDS) only for hazardous substances and mixtures/preparations. Mineral wool products (panels or rolls), are articles under REACH and therefore, MSDS is not legally required. Nevertheless, URSA Insulation decides to provide its customers with the appropriate information for assuring safe handling and use of mineral wool

|   |                          |                                   |
|---|--------------------------|-----------------------------------|
|  | Standard                 | <b>Date:</b><br><b>15.01.2010</b> |
|   | <b>Safety Data Sheet</b> | Version 1                         |
|   |                          | Page: 5 / 6                       |

## 11. TOXICOLOGICAL INFORMATION

|                            |  |
|----------------------------|--|
| <b>Acute effect</b>        | : The mechanical effect of fibres in contact with the skin can cause a temporary itching.  |
| <b>Carcinogenic effect</b> | : Classification not applicable for mineral wools in this product; in accordance with the directive 97/69/EC and European Regulation 1272/2008, nota Q. (See Section 15) |

## 12. ECOLOGICAL INFORMATION

This product is not expected to cause harm to animals or plants during normal conditions of use.

## 13. DISPOSAL CONSIDERATIONS

|   |   |
|---|---|
| <b>Waste from residue</b>                           | : Dispose of in accordance with regulations and procedures in force in country of use or disposal |
| <b>Dirty packaging</b>                              | : Dispose of in accordance with local regulations.  |
| <b>Code from European Waste Catalogue:</b> 17 06 04 |   |

## 14. TRANSPORT INFORMATION


**International regulations** : No specific regulations

## 15. REGULATORY INFORMATION

The European directive 97/69/EC replaced by the regulation (EC) n° 1272/2008 concerning the classification, labelling and packaging of the substance and the mixtures does not classify glass fibres as hazardous, if they are in compliance with the note Q of this Regulation.

The note Q specifies that classification as carcinogenic does not apply if:

- a short-term bio persistence test by inhalation has shown that fibres longer than 20µm have a weight half life less than 10 days, or
- a short-term bio persistence test intra-tracheal instillation has shown fibres longer than 20 µm have a weighted half life less than 40 days, or
- an appropriate intra-peritoneal test has shown no evidence of excess carcinogenicity, or
- a suitable long term inhalation test has shown absence of relevant pathogenicity or neoplastic changes.

|   |                          |                                   |
|---|--------------------------|-----------------------------------|
|  | Standard                 | <b>Date:</b><br><b>15.01.2010</b> |
|   | <b>Safety Data Sheet</b> | Version 1                         |
|   |                          | Page: 6 / 6                       |

## 16. OTHER INFORMATION

The glass wool fibres of this product are exonerated from the carcinogenic classification according to the European directive 97/69/CE and the Regulation (EC) 1272/2008 if they fulfil one of the criteria of the nota Q of these texts.

All products manufactured by Cie name are made of non-classified fibres and are certified by EUCEB.

EUCEB, European Certification Board of Mineral Wool Products - [www.euceb.org](http://www.euceb.org), is a voluntary initiative by the mineral wool industry. It is an independent certification authority that guarantees that products are made of fibres, which comply with the exoneration criteria for carcinogenicity (Note Q) of the Directive 97/69/EC and the Regulation (EC) 1272/2008.

To ensure that fibres comply with the exoneration criteria all tests and supervision procedures are carried out by independent, expert qualified institutions. EUCEB ensures that the producers of mineral wool have put in place self-control measures.

The mineral wool producers commit to EUCEB to:

- supply sampling and analysis reports established by laboratories recognized by EUCEB, proving that the fibres comply with one of the four criteria of exoneration described in Note Q of the Directive 97/99/EC,
- be controlled, twice per year, of each production unit by an independent third party recognized by EUCEB (sampling and conformity to the initial chemical composition),
- put in place procedures of internal self-control in each production unit.

The products responding to the EUCEB certification are recognized by the EUCEB logo put on the packaging.



EUCEB is an ISO 9001:2000 certified association.

Moreover, in 2001, the International Agency for Research on Cancer, re-evaluated and reclassified mineral wool (insulation glass wool, rock(stone) wool and slag wool) from Group 2B (possibly carcinogenic) to Group 3 «agent which cannot be classified as for their carcinogenicity to humans». (See Monograph Vol 81, <http://monographs.iarc.fr/>)

*Person who wish to obtain more detailed information have to contact the producer (address on the first page of this sheet).*

*Information given in this document is on the state of our knowledge regarding this material as of January 15th, 2010.*

*It is given in good faith.*

*The attention of users is drawn to possible risks taken when the product is used for other application than the ones it has been designed for*